



The BWA1L14 1 line alphanumeric pager offers 14 large characters display. It can also be programmed as a front display numeric pager.

URGENT CALL feature allows first priority calls to override any alert and notify user with a Tone + Vibrate signal.

- Hand and PC programmable.
- Selectable Backlight.
- Real Time Clock.
- Repeat Message Indicator.
- Scrolling Display.
- Low Battery Reminder.
- Urgent Call Feature.
- Unread Message indicator.
- In Range, out of range indicator.
- Selectable Functions.
- Multiple Alert.
- Alarm clock Function.

### Specifications

Frequency Range:	VHF: 143-150MHz 151-159MHz UHF: 454-460MHz 460-466MHz 466-472MHz
Cap Codes:	4
Receiver Type:	Synthesized
Baud Rate:	512, 1200, 2400 bps
Paging Sensitivity	5uV/m @ 512 bps 7 uV/m @ 1200 bps 9uV/m @ 2400 bps
Channel Spacing:	25KHz
Frequency Deviation:	+/-4.5KHz
Frequency Stability:	+/- 10ppm
Selectivity:	> 55dB
Image Rejection:	> 50dB
Spurious Rejection:	> 50dB
Intermodulation:	> 55dB
Alert Tone Loudness:	80dB+ @ 12 inch
Display:	14 character backlit with icons
Memory Capacity:	16 messages max 840 characters max message length 120 characters
Messages:	16
Weight:	45 with battery (1.6oz)
Dimensions:	68 x 46 x 21mm 2.7 x 1.8 x 0.8 inch
Battery Type:	Single AAA
Low Battery Alert Level:	1.1V
Operating Temperature:	-10° to 50° C

\*Other frequency ranges available upon request

